

VERDI S3

AC880BP

CE UNI EN ISO 20345:2012 S3 SRC

High safety shoe, water-resistant WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*


Size 36-49 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

-  FARMING AND MINING
-  COMPONENTS AND AUTOMOTIVE
-  WOOD METAL CARPENTRY
-  BUILDING AND HEAVY INDUSTRY
-  LOGISTICS AND LIGHT INDUSTRY

SOLE

Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.



ANTISLIPPING TEST RESULTS

**SRC**

ANTI-SLIPPING SOLE

SRA		
ceramic +	HEEL >= 0,28	0,39
NaLS	FLAT >= 0,32	0,36

SRB		
steel +	HEEL >= 0,13	0,26
glycerol	FLAT >= 0,18	0,22